

# DUAL AUGER 1121

## SPECIFICATIONS

Model	1121		
Undercarriage	Tracks	Flotation Tires	Row Crop Tires
<b>Specifications</b>			
Heaped capacity*	1125 bu.	1100 bu.	1100 bu.
Unload speed - maximum**	550 bu/min	550 bu/min	550 bu/min
Total weight - empty	26,620 lbs.	20,880 lbs.	21,440 lbs.
Hitch weight - empty	3,820 lbs.	3,820 lbs.	3,820 lbs.
Hitch weight - loaded	6,260 lbs.	6,260 lbs.	6,260 lbs.
Width - overall	12'-0"	12'-2"	12'-0"
Length - overall	30'-9"	30'-9"	30'-9"
Height - short side	11'-0"	11'-0"	11'-0"
Height - high side	12'-0"	12'-0"	12'-0"
<b>Tractor Requirements (minimum)</b>			
Tractor horsepower	250 hp	250 hp	250 hp
Tractor hydraulics	3 SCVs; 2,320 system psi	3 SCVs; 2,320 system psi	3 SCVs; 2,320 system psi
<b>Features and options</b>			
Vertical auger	STD with 20" diameter flighting with a 22" diameter tube		
Horizontal auger	STD with 20" diameter flighting with a 22" diameter tube		
Gearbox	STD with 90 degree, 3.5" - 4" pitch cut gears, 2:1 ratio		
Drive belts	STD with two 4-band, multi-strand V-belts		
Drive sheaves	STD with 8-groove 7-1/2" diameter drive and 15" diameter driven sheaves		
PTO	STD with 1-3/4" diameter, 20 spline, 1000 rpm PTO		
Tracks	OPT; 36" x 100" contact area	---	---
Flotation tires	---	OPT; 1245/50R32	---
Row crop tires	---	---	OPT; 480/80 R42
3-point scale package	OPT	OPT	OPT
GT400 scale display	OPT	OPT	OPT
GT560 Autolog scale display	OPT	OPT	OPT
Remote scale readout	OPT	OPT	OPT
Roll tarp - manual	STD	STD	STD
Safety chains	STD	STD	STD
Adjustable spout	STD	STD	STD

\*Cart capacity and hitch weight are based on #2 corn at 15% moisture (56lb test weight). Cart capacity and hitch weight may vary based on crop type, grade, moisture and other environmental factors.

\*\*Approximate with 15% moisture corn. Bushels/minute will vary with moisture content of grain and/or PTO rpm.



# CORNER SINGLE AUGER 1051

## SPECIFICATIONS

Model	1051	
Undercarriage	Tracks	Flotation Tires
<b>Specifications</b>		
Heaped capacity*	1050 bu.	1050 bu.
Unload speed - maximum**	475 bu/min	475 bu/min
Total weight - empty	23,000 lbs.	15,100 lbs.
Hitch weight - empty	2,500 lbs.	2,500 lbs.
Hitch weight - loaded	5,000 lbs.	5,000 lbs.
Width - grain tank	12'-4"	12'-4"
Length - grain tank	19'-3"	19'-3"
Height - short side	11'-7"	11'-7"
Height - high side	12'-7"	12'-7"
Length - overall	30'-4"	30'-4"
<b>Tractor Requirements (minimum)</b>		
Tractor horsepower	250 hp	250 hp
Tractor hydraulics	3 SCVs; 2,320 system psi	3 SCVs; 2,320 system psi
<b>Features and options</b>		
Vertical auger	STD with 20" diameter flighting with a 21" diameter tube	
Gearbox	STD with 90 degree, 3.5" - 4" pitch cut gears, 2:1 ratio	
PTO	STD with 1-3/4" diameter, 20 spline, 1000 rpm PTO	
Tracks	OPT; 36" x 100" contact area	---
Diamond tread tires	---	OPT; 900/60 R32
Lug tread tires	---	OPT; VF 1050/50 R32
5-point scale package	OPT	OPT
GT400 scale display	OPT	OPT
GT560 Autolog scale display	OPT	OPT
Remote scale readout	OPT	OPT
Roll tarp - manual	OPT	OPT
Safety chains	STD	STD
Adjustable spout	STD	STD
<p>*Cart capacity and hitch weight are based on #2 corn at 15% moisture (56lb test weight). Cart capacity and hitch weight may vary based on crop type, grade, moisture and other environmental factors.</p> <p>**Approximate with 15% moisture corn. Bushels/minute will vary with moisture content of grain and/or PTO rpm.</p>		

